



# JAKARTA EE

Jakarta Data  
*Query by Method Name Extension*

1.0, May 08, 2024: FINAL

# Table of Contents

Copyright .....	2
Eclipse Foundation Specification License - v1.1 .....	2
Disclaimers .....	2
1. Introduction .....	3
2. Query by Method Name .....	4
2.1. Limits .....	4
2.2. Restrictions .....	4
2.3. Orders .....	4
2.4. Example query methods .....	4
2.5. BNF Grammar for Query Methods .....	5
2.6. Query by Method Name Keywords .....	6
2.7. Query by Method Name Conditions .....	7
2.8. Return Types .....	9
2.9. Persistent Field Names in Query by Method Name .....	9
2.9.1. Scenario 1: Person Repository with Unambiguous Resolution .....	10
2.9.2. Scenario 2: Customer Repository with Resolution that requires a Delimiter .....	10

Specification: Jakarta Data

Version: 1.0

Status: FINAL

Release: May 08, 2024

## Copyright

Copyright (c) 2022, 2024 Eclipse Foundation.

### Eclipse Foundation Specification License - v1.1

By using and/or copying this document, or the Eclipse Foundation document from which this statement is linked or incorporated by reference, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions:

Permission to copy, and distribute the contents of this document, or the Eclipse Foundation document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the document, or portions thereof, that you use:

- link or URL to the original Eclipse Foundation document.
- All existing copyright notices, or if one does not exist, a notice (hypertext is preferred, but a textual representation is permitted) of the form: "Copyright (c) [\$date-of-document] Eclipse Foundation AISBL <https://www.eclipse.org/legal/efsl.php> "

Inclusion of the full text of this NOTICE must be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of Eclipse Foundation documents is granted pursuant to this license, except anyone may prepare and distribute derivative works and portions of this document in software that implements the specification, in supporting materials accompanying such software, and in documentation of such software, PROVIDED that all such works include the notice below. HOWEVER, the publication of derivative works of this document for use as a technical specification is expressly prohibited.

The notice is:

"Copyright (c) 2022, 2024 Eclipse Foundation AISBL. This software or document includes material copied from or derived from Jakarta Data and <https://jakarta.ee/specifications/data/>."

### Disclaimers

THIS DOCUMENT IS PROVIDED "AS IS," AND TO THE EXTENT PERMITTED BY APPLICABLE LAW THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION AISBL MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

TO THE EXTENT PERMITTED BY APPLICABLE LAW THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION AISBL WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of the copyright holders or the Eclipse Foundation AISBL may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

## Chapter 1. Introduction

*Query by Method Name* is a query language suitable for embedding in the names of methods written in Java. As such, its syntax is limited to the use of legal identifier characters, so the text of a query must contain neither whitespace, nor punctuation characters, nor numeric operators, nor comparison operators.

Jakarta Data 1.0 offers a Query by Method Name facility as an extension to the specification, providing a migration path for existing applications written for repository frameworks which offer similar functionality.

```
@Repository
public interface ProductRepository extends BasicRepository<Product, Long> {

    List<Product> findByName(String name);

    @OrderBy("price")
    List<Product> findByNameLike(String namePattern);

    List<Product> findByNameLikeAndPriceLessThanOrderByPriceDesc(String namePattern, float priceBelow);
}
```

The functionality described here overlaps significantly with both:

- parameter-based automatic query methods, that is, @Find and @Delete, and
- annotated query methods, that is @Query and Jakarta Data Query Language or Jakarta Persistence Query Language.

Therefore, these alternative approaches are strongly preferred for newly-written code.

A Jakarta Data provider is required to support the Query by Method Name extension in Jakarta Data 1.0.



A Jakarta Data provider backed by a key-value or wide-column datastore is not required to support Query by Method Name.



This functionality is considered deprecated, and the requirement that a provider support the Query by Method Name extension will be removed in a future version of Jakarta Data.

## Chapter 2. Query by Method Name

In Query by Method Name, a query is expressed via a set of method naming conventions.

A method name is formed by concatenating, in the following order:

- an *action*, which must be `find`, `delete`, `count`, or `exists`,
- an optional `limit`,
- a optional `restriction`, and
- an optional `order`.

### 2.1. Limits

A `find` query may have a *limit*, for example, `First` or `First10`. Other actions must not be combined with a limit.

The limit determines the maximum number of records which may be returned by the query. If the query has an order, then the records which are returned are those which occur first after sorting.

### 2.2. Restrictions

A *restriction* specifies the criteria used to filter records. It is formed by concatenating `By` with one or more conditions, delimited by `And` or `Or`, for example, `PriceLessThanAndNameLike`.

Each *condition* is formed by concatenating, in the following order:

- a property name, which may be a compound name, as specified below in [Persistent Field Names in Query by Method Name](#),
- optionally, `IgnoreCase` (for text properties),
- optionally, `Not`,
- optionally, an operator such as `LessThan` or `Like`.

Absence of an operator implies the equality condition.

The conditions belonging to the restriction determine the parameters of the method, as specified below in [Query by Method Name Conditions](#).

### 2.3. Orders

A `find` query may have an *order*. The *order* specifies how records must be sorted. It is formed by concatenating `OrderBy` with one or more ordered pairs of an entity attribute name and a direction of sorting, `Asc` or `Desc`. The direction may be omitted if there is only one property, in which case `Asc` is implied.

The order is lexicographic, that is, ordered pairs occurring earlier take precedence. An ordered pair occurring later is only used to resolve "ties" between records which cannot be unambiguously ordered using only earlier ordered pairs.

If no order is specified, the records are not sorted.

### 2.4. Example query methods

The following table displays some examples of legal method signatures.

<code>findByName(String name)</code>	Find entities by the <code>name</code> property.
--------------------------------------	--

<code>findByAgeGreaterThan(int age)</code>	Find entities where age is greater than the specified value.
<code>findByAuthorName(String authorName)</code>	Find entities by the <code>authorName</code> property of a related entity.
<code>findByCategoryNameAndPriceLessThan(String categoryName, double price)</code>	Find entities by <code>categoryName</code> and <code>price</code> properties, applying an <code>And</code> condition.
<code>findByNameLikeOrderByPriceDescIdAsc</code>	Find entities by matching the <code>name</code> property against a pattern, sorting the results by <code>price</code> in descending order, and sorting results with the same <code>price</code> by the <code>id</code> in ascending order.

## 2.5. BNF Grammar for Query Methods

The rules for parsing an interpreting a method name are specified by the following grammar.

```

query : find | action
find : "find" limit? ignoredText? restriction? order?
action : ("delete" | "count" | "exists") ignoredText? restriction?
restriction : "By" predicate
limit : "First" max?
predicate : condition (("And" | "Or") condition)*
condition : property "IgnoreCase"? "Not"? operator?
operator
    : "Contains"
    | "EndsWith"
    | "StartsWith"
    | "LessThan"
    | "LessThanEqual"
    | "GreaterThan"
    | "GreaterThanEqual"
    | "Between"
    | "Like"
    | "In"
    | "Null"
    | "True"
    | "False"
property : identifier ("_" identifier)*
identifier : word
max : digit+
order : "OrderBy" (property | orderItem+)
orderItem : property ("Asc" | "Desc")

```

Quoted names are considered case-sensitive keywords.

*Table 1. Explanation of the BNF elements*

Rule name	Explanation
<code>query</code>	May be a <code>find</code> query, or a <code>delete</code> , <code>count</code> , or <code>exists</code> operation.
<code>find</code>	A <code>find</code> query has an optional <code>limit</code> and optional <code>restriction</code> on records to be retrieved, and optional <code>sorting</code> .
<code>action</code>	Any other kind of operation has only a <code>restriction</code> to a subset of records.
<code>restriction</code>	Restricts the records returned to those which satisfy a <code>predicate</code>
<code>limit</code>	Limits the records retrieved by a <code>find</code> query to a hardcoded maximum, such as <code>First10</code> .

Rule name	Explanation
ignoredText	Optional text that does not contain <code>By</code> , <code>All</code> , or <code>First</code> .
predicate	A filtering criteria, which may include multiple conditions separated by <code>And</code> or <code>Or</code> .
condition	A property of the queried entity and an operator.
operator	An operator belonging to a condition, for example, <code>Between</code> or <code>LessThan</code> . When absent, equality is implied.
property	A property name, which can include underscores for nested properties.
identifier	A legal Java identifier, not containing an underscore.
max	A positive whole number.
order	Specifies that results of a <code>find</code> query should be sorted lexicographically, with respect to one or more order items.
orderItem	A field used to sort results, where <code>Asc</code> or <code>Desc</code> specifies the sorting direction.

## 2.6. Query by Method Name Keywords

An implementation of Query by Method Name must support the following types of operation.

*Table 2. Query by Method Name Actions*

Action	Description
<code>find</code>	Returns entity instances representing the records which satisfy the restriction, or representing all records if there is no restriction.
<code>delete</code>	Deletes every record which satisfy the restriction, or all records if there is no restriction, and returns either no result ( <code>void</code> ) or the number of records deleted.
<code>count</code>	Returns the number of records which satisfy the restriction, or the total number of records if there is no restriction.
<code>exists</code>	Returns <code>true</code> if at least one record satisfies the restriction or if there is at least one record in the database when there is no restriction.

An implementation of Query by Method Name must support the following keywords.

*Table 3. Query by Method Name Keywords*

Keyword	Description	Method signature example
<code>And</code>	The <code>And</code> operator requires both conditions to match.	<code>findByNameAndYear</code>
<code>Or</code>	The <code>Or</code> operator requires at least one of the conditions to match.	<code>findByNameOrYear</code>



Keyword	Description	Method signature example
Not	Negates the condition that immediately follows the Not keyword. When used without a subsequent keyword, means not equal to.	findByNameNotLike
First	For a query with ordered results, limits the quantity of results to the number following First, or if there is no subsequent number, to a single result.	findFirst10By
OrderBy	Specify a static sorting order followed by one or more ordered pairings of a property path and direction (Asc or Desc). The direction Asc can be omitted from the final property listed, in which case ascending order is implied for that property.	findByAgeOrderByHeightDescIdAsc findByAgeOrderById
Desc	Specify a static sorting order of descending.	findByNameOrderByAgeDesc
Asc	Specify a static sorting order of ascending.	findByNameOrderByAgeAsc

For relational databases, the logical operator `And` takes precedence over `Or`, meaning that `And` is evaluated on conditions before `Or` when both are specified on the same method. For other database types, the precedence is limited to the capabilities of the database. For example, some graph databases are limited to precedence in traversal order.



An implementation of Query by Method Name backed by a document or graph database is not required to support the `First` keyword. A repository method must raise `java.lang.UnsupportedOperationException` or a more specific subclass of the exception if the database does not support this functionality.

## 2.7. Query by Method Name Conditions

In addition to equality conditions, Query by Method Name defines the following kinds of condition.

Table 4. Query by Method Name Conditions

Keyword	Property type	Parameters	Description	Method signature example
Between	Any sortable type	2	Find results where the property is between (inclusive of) two given values, with the first value being the inclusive minimum and the second value being the inclusive maximum.	findByDateBetween
Contains	String	1	Matches string values with the given substring, which can be a pattern.	findByProductNameContains
EndsWith	String	1	Matches String values with the given ending, which can be a pattern.	findByProductNameEndsWith

Keyword	Property type	Parameters	Description	Method signature example
LessThan	Any sortable type	1	Find results where the property is less than the given value	findByAgeLessThan
GreaterThan	Any sortable type	1	Find results where the property is greater than the given value	findByAgeGreaterThan
LessThanEqual	Any sortable type	1	Find results where the property is less than or equal to the given value	findByAgeLessThanEqual
GreaterThanEqual	Any sortable type	1	Find results where the property is greater than or equal to the given value	findByAgeGreaterThanEqual
Like	String	1	Matches string values against the given pattern.	findByTitleLike
IgnoreCase	String		Requests that string values be compared independent of case for query conditions and ordering.	findByStreetNameIgnoreCaseLike
In	Any type	1 Set	Find results where the property is one of the values that are contained within the given Set.	findByIdIn
Null	Any type	0	Finds results where the property has a null value.	findByYearRetiredNull
StartsWith	String	1	Matches String values with the given beginning, which can be a pattern.	findByFirstNameStartsWith
True	Boolean or boolean	0	Finds results where the property has a boolean value of true.	findBySalariedTrue
False	Boolean or boolean	0	Finds results where the property has a boolean value of false.	findByCompletedFalse

Most *Query by Method Name* conditions require a single repository method parameter. The *Between* condition requires two parameters. *Null*, *True*, and *False* require none. An *In* condition requires a parameter of type `Set<T>` where `T` is the type of the property. The repository method parameters used for *Query by Method Name* conditions follow the order in which the *Query by Method Name* conditions appear within the method name.

Wildcard characters for patterns are determined by the data store. For relational databases, `_` matches any one character and `%` matches zero or more characters.



An implementation of *Query by Method Name* backed by a document or graph database is not required to support *Contains*, *EndsWith*, *StartsWith*, *Like*, *IgnoreCase*, *In*, or *Null*. A repository method must raise `java.lang.UnsupportedOperationException` or a more specific subclass of the exception if the database does

not provide the requested functionality.

In the following example the value of the first parameter, `namePattern`, is used for `NameLike`, the values of the second and third parameters, `minYear` and `maxYear`, are used for `YearMadeBetween`, and the value of the fourth parameter, `maxPrice`, is used for `PriceLessThan`.

```
List<Product> findByNameLikeAndYearMadeBetweenAndPriceLessThan(String namePattern,
                                                                int minYear,
                                                                int maxYear,
                                                                float maxPrice,
                                                                Limit limit,
                                                                Order<Product> sortBy)
```

## 2.8. Return Types

The return type of a Query by Method Name is determined as indicated in the following table, where E is the queried entity type.

Table 5. Repository Method Return Types

Operation	Return type	Notes
count	long	
delete	void, long, int	
exists	boolean	
find	E or Optional<E>	For queries returning a single item (or none)
find	E[] or List<E>	For queries where it is possible to return more than one item
find	Stream<E>	The caller must call <code>java.util.stream.BaseStream.close()</code> for every stream returned by the repository method
find accepting a PageRequest	Page<E> or CursoredPage<E>	For use with pagination

## 2.9. Persistent Field Names in Query by Method Name

Section 3.2 of the Jakarta Data specification describes how names are assigned to persistent fields of an entity.

For Query by Method Name, the use of delimiters within a compound name is optional. Delimiters may be omitted entirely from a compound name when they are not needed to disambiguate the persistent field to which the name refers. But for a given entity property name, delimiter usage must be consistent: either the delimiter must be used between every pair of persistent field names within the compound name, or it must not occur within the compound name.

Resolution of a persistent field involves the following steps:

1. A persistent field name is extracted from the method name according to the [BNF Grammar for Query Methods](#). For example, if the query method name is `findByAddressZipCode`, the extracted field name is `AddressZipCode`.
2. The extracted name is matched against the fields of the entity class. If the name assigned to a persistent field of the entity class matches the extracted name, ignoring case, then the extracted name resolves to that field.
3. Otherwise, if no match is found among the fields of the entity, the extracted name is matched against the fields of

entity classes and embedded classes reachable from the entity class, interpreting the extracted name as a compound name, as outlined in the previous section, both with and without the optional delimiter. If the compound name assigned to a persistent field matches the extracted name, also interpreted as a compound name, and ignoring case, then the extracted name resolves to that field.

4. If no matching persistent field is found in either of the previous steps, the provider is permitted to reject the query method or to throw `UnsupportedOperationException` when the method is called.

A persistent field name used in a *Query by Method Name* must not contain a keyword reserved by the [grammar](#).

### 2.9.1. Scenario 1: Person Repository with Unambiguous Resolution

In this scenario, we have the following data model:

```
class Person {
    private Long id;
    private MailingAddress address;
}

class MailingAddress {
    private int zipcode;
}
```

The `Person` entity does not have an `addressZipCode` field, so use of the delimiter is optional. It is valid to write both of the following repository methods, which have the same meaning,

```
List<Person> findByAddressZipCode(int zipCode);
List<Person> findByAddress_zipcode(int zipCode);
```

### 2.9.2. Scenario 2: Customer Repository with Resolution that requires a Delimiter

In this scenario, we have the following data model:

```
class Customer {
    private Long id;
    private String addressZipCode;
    private MailingAddress address;
}

class MailingAddress {
    private int zipcode;
}
```

The `Customer` entity has an `addressZipCode` field, as well as an `address` field for an embeddable class with a `zipcode` field. The method name `findByAddressZipCode` points to the `addressZipCode` field and cannot be used to navigate to the embedded class. To navigate to the `zipcode` field of the embedded class, the delimiter must be used:

```
List<Customer> findByAddress_zipcode(int zipCode);
```